



Spatial modulation conjugate to the target plane: beamshaping, micromanipulation and microscopy

Palima, Darwin; Villangca, Mark Jayson; Bañas, Andrew Rafael; Kopylov, Oleksii; Glückstad, Jesper

Publication date:
2015

[Link back to DTU Orbit](#)

Citation (APA):

Palima, D., Villangca, M. J., Bañas, A. R., Kopylov, O., & Glückstad, J. (2015). *Spatial modulation conjugate to the target plane: beamshaping, micromanipulation and microscopy*. Abstract from Northern Optics and Photonics 2015, Lappeenranta, Finland.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

SPATIAL MODULATION CONJUGATE TO THE TARGET PLANE: BEAMSHAPING, MICROMANIPULATION AND MICROSCOPY

Darwin Palima, Mark Jason Villangca, Andrew Rafael Bañas,

Oleksii Kopylov and Jesper Glückstad

DTU Fotonik, Department of Photonics Engineering

Technical University of Denmark, Kgs. Lyngby, Denmark

Contact: dazp@fotonik.dtu.dk

Keywords: beam shaping, optical trapping and micromanipulation, Generalized phase contrast, Fourier optics and signal processing

Creating novel laser sources enables control over the energy of emitted photons, $E = \hbar\omega$, which, in turn, enhances control over light-matter interactions that are governed by energy conservation principles. Similarly, exploiting conservation of momentum means that spatial light modulation is needed to gain better control over light's momentum (linear, $\vec{p} = \hbar\vec{k}$, spin or orbital angular momentum $S_z = \pm\hbar$ and $L_z = \pm m\hbar$), respectively). Using a spatial light modulator (SLM) as a diffractive optical element gives access to the constituent wave vectors that are then combined to form the desired beam pattern. However, placing the SLM conjugate to the target plane where the beam should be formed also offers some advantages. In this paper, we show that this latter geometry has promising applications in beamshaping [1], optical trapping and micromanipulation [2] and microscopy [3], among others.

Generalized Phase Contrast (GPC) places a phase-only spatial light modulator at the input plane of a $4f$ optical processing geometry. A static phase contrast filter (PCF) placed at the spatial frequency plane effectively synthesizes a reference wave to have a common-path interferometer that transforms input phase patterns into high-contrast intensity patterns at the output plane. This simplifies the generation of various light patterns since the needed spatial phase modulation directly mimics the desired pattern. Moreover, using the same input phase mask and PCF maintains high efficiency and image fidelity over a range of input wavelengths as demonstrated by successful GPC lightshaping of a supercontinuum source (see Fig. 1, adapted from [1]).

Our Biophotonics WorkStation (BWS) projects matched counter-propagating patterns to create multiple dual-beam traps that can grab and mechanically control multiple targets such as, for instance, the optical handles of designed microstructures that are fabricated by two-photon photopolymerization. When the optically trapped microstructures are equipped with embedded waveguides, we get so-called wave-guided optical waveguides that can redirect and reshape light (see Fig. 2, adapted from [2]). Building upon the convenient generation of trapping patterns using an SLM conjugate to the target plane, a hybrid system that incorporates an auxiliary system that uses diffractive elements to dynamically control the coupling beam enables it to follow and maintain efficient coupling as the waveguide is manipulated in 3D.

Finally, placing a phase-only SLM conjugate to the object/image plane of a microscope enables one to create a “phase ruler” for phase measurements in microscopy. Controlling the SLM pattern and phase step provides direct phase measurement when the combined field is visualized in a subsequent phase imaging system by simply noting the SLM phase that cancels the object phase (e.g., see Fig. 3).




Fig. 1: GPC lightshaping a Supercontinuum source




Fig. 2: Optically trapped light-guiding microstructures




Fig. 3: Phase measurement in microscopy

1. O. Kopylov, A. Bañas, M. Villangca, D. Palima, and J. Glückstad, "GPC light shaping a supercontinuum source," *Opt. Express* **23**, 1894-1905 (2015).
2. M. Villangca, A. Bañas, D. Palima and J. Glückstad, "Dynamic diffraction-limited light-coupling of 3D-maneuvered wave-guided optical waveguides," *Opt. Express* **22**, 17880-17889 (2014)
3. D. Palima and J. Glückstad, "Diffractive generalized phase contrast for adaptive phase imaging and optical security," *Opt. Express* **20**, 1370-1377 (2012).